## **Technical Data Sheet**

Bondloc B7774 – Belt Dressing Revised 03.08.10



# **Bondloc B7774 Belt Dressing**

#### PRODUCT DESCRIPTION

B7774 effectively boosts the performance of "V", flat and round drive belts by reducing slippage, thereby extending belt life, reducing energy needs and the noise associated with slipping belts.

#### **APPLICATIONS**

B7774 can be used on all drive belts, such as "V", flat and round.

#### **USEFUL HINTS**

- Highly tacky product effectively reduces slippage
- · Suitable for all drive belts
- Increases belt life
- Boosts transmitted power by up to 50%
- Helps in the reduction of energy costs
- High adhesion prevents thrown off
- Resistant to oxidisation
- · Easily removed.

#### INSTRUCTIONS FOR USE

Shake can well before use. Spray from 25-30cm ensuring an even coating over the whole surface. Slippage will decrease as product is distributed.

#### **STORAGE**

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

### **TECHNICAL FEATURES**

| Appearance        | Clear tacky low viscosity fluid  |
|-------------------|--|
| Odour             | Low odour after solvent has evaporated   |
| Contents          | Blend of synthetic polymer plasticiser, naphtha solvent and hydrocarbon propellants. No silicones. |
| Solubility        | Insoluble in water   |
| Storage           | Below 50°C   |
| Flash Point       | < 0°C  |
| Relative Gravity  | 0.673  |
| Temperature range | Up to 130°C  |

#### **HEALTH & SAFETY IN USE**

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on to an open flame or any incandescent material. Keep away from sources of ignition. This technical information sheet for does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understand the MSDS.

#### **PRESENTATION**

Aerosol 400m