



Technical Data Sheet

Auto740 Maintenance Spray

PRODUCT DESCRIPTION

Bondloc Maintenance Spray with premium lubricating, dewatering, cleaning, penetrating and corrosion inhibition properties.

Supplied in a 360 degree rotational can which includes the permanently attached "Easy Straw" for ease of use and convenience.

APPLICATIONS

B7740 can be used on all ferrous metals for the removal and freeing of seized/corroded nuts and bolts, hinges, locks, tools and fittings.

USEFUL NOTES

- Long lasting lubrication
- Moisture displacement
- Moisture repellency
- Leaves a protective film to guard against corrosion
- Low viscosity for maximum penetration
- Easy to apply and works quickly
- Contains PTFE for increased lubrication and load bearing resistance.
- Enhanced operating temperature range

INSTRUCTIONS FOR USE

Shake can thoroughly before use. Spray from 15-30cm on to part and allow to penetrate or form a film.

STORAGE

Store product in a dry location and out of direct sunlight. Optimal storage : 8 °C to 20 °C

TECHNICAL FEATURES

Appearance	Almost clear, liquid drying to a thin greasy state.
Viscosity	Thin Liquid
Specific gravity	0.76 – 0.81
Non-volatile % m/m	70-90
Active Content % m/m	20-30
Flammability	Extremely flammable, flash point below -20°C
Service Temperature	Up to 80 °C – Continuous
	Up to 150 °C - Intermittent
	Down to -40 °C
Odour	Pleasant fragrance
Contents / Composition	Blend of naphthenic oil, modified grease, water displacing additives and wetting agents, and PTFE in naphtha (petroleum) hydrocarbon heavy, in butane/isobutane propane propellant. No silicones or chlorinated solvents.
Solubility	Insoluble in water
Storage	8 °C to 20 °C

HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

PACKAGING FORMAT

500ml

Bondloc UK Ltd.
Units 1 & 2
Bewdley Business Park
Bewdley, Worcestershire
DY12 2TZ, UK

+44 (0) 1299 269 269
sales@bondloc.co.uk

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.

